

GREASELIFT**Section: 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING****1.1 Product identifier**

Product name : GREASELIFT

Product code : 116864E

Use of the Substance/Mixture : Grill Cleaner

Substance type: : Mixture

For professional users only.

Product dilution information : 16.8 %

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Kitchen cleaner. Manual process
Oven/Grill Cleaner. Manual process
Oven/Grill Cleaner. Spray and wipe manual process

Recommended restrictions on use : Reserved for industrial and professional use.

1.3 Details of the supplier of the safety data sheet

Company : Ecolab Ltd.
PO Box 11; Winnington Avenue
Northwich, Cheshire, United Kingdom CW8 4DX
+ 44 (0)1606 74488
ccs@ecolab.com

1.4 Emergency telephone number

Emergency telephone number : +441618841235
+32-(0)3-575-5555 Trans-European

Poison Information Centre telephone number : For medical professionals only: 0344 892 0111

Date of Compilation/Revision : 07.11.2022
Version : 5.0

Section: 2. HAZARDS IDENTIFICATION**2.1 Classification of the substance or mixture****Classification (REGULATION (EC) No 1272/2008)****Product AS SOLD**

|| Acute toxicity, Category 4

H332

GREASELIFT

Skin corrosion, Category 1
Serious eye damage, Category 1

H314
H318

Product AT USE DILUTION

Not a hazardous substance or mixture.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Product AS SOLD

Hazard pictograms

:



Signal Word

: Danger

Hazard Statements

: H314
H332

Causes severe skin burns and eye damage.
Harmful if inhaled.

Precautionary Statements

: **Prevention:**
P280

Wear protective gloves/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

Hazardous components which must be listed on the label:

Benzyl alcohol
2-butoxyethanol
isopropanolamine
2-(2-aminoethoxy)ethanol

Product AT USE DILUTION

Not a hazardous substance or mixture.

Additional Labelling:

Product AS SOLD

Special labelling of certain mixtures : Not applicable.

Product AT USE DILUTION

Special labelling of certain mixtures : Safety data sheet available on request.

2.3 Other hazards

Product AS SOLD

None known.

Section: 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixtures

GREASELIFT**Product AS SOLD
Hazardous components**

| Chemical Name | CAS-No. EC-No. REACH No. | Classification REGULATION (EC) No 1272/2008 | Concentration : [%] |
|--|---|--|------------------------|
| Benzyl alcohol | 100-51-6 202-859-9 01-2119492630-38 | Acute toxicity Category 4; H302 Acute toxicity Category 4; H332 Serious eye damage/eye irritation Category 2; H319 | >= 30 - < 50 |
| 2-butoxyethanol | 111-76-2 203-905-0 01-2119475108-36 | Acute toxicity Category 4; H302 Acute toxicity Category 3; H331 Skin irritation Category 2; H315 Eye irritation Category 2; H319 | >= 5 - < 10 |
| 9-octadecenoic acid (z)-, compd. with 2- aminoethanol (1:1) | 2272-11-9 218-878-0 01-2119958940-28 | Eye irritation Category 2; H319 | >= 5 - < 10 |
| Poly(oxy-1,2-ethanediyl), .alpha.-(phenylmethyl)- .omega.-hydroxy- | 26403-74-7 | Eye irritation Category 2; H319 | >= 5 - < 10 |
| isopropanolamine | 78-96-6 201-162-7 01-2119475331-43 | Skin corrosion Category 1B; H314 | >= 5 - < 10 |
| 2-(2-aminoethoxy)ethanol | 929-06-6 213-195-4 01-2119520701-52 | Skin corrosion Sub-category 1B; H314 Serious eye damage Category 1; H318 | >= 5 - < 10 |
| Benzenesulfonic acid, C10-16-alkyl derivs., potassium salts | 68584-27-0 271-534-1 REACH EXEMPTED | Acute toxicity Category 4; H302 Eye irritation Category 2; H319 | >= 2.5 - < 5 |
| Linear(C12-C14)alkanol, ethoxylated, sulfated, sodium salt | 68891-38-3 500-234-8 01-2119488639-16 | Skin irritation Category 2; H315 Serious eye damage Category 1; H318 Chronic aquatic toxicity Category 3; H412 Serious eye damage/eye irritation Category 1 10 - 100 % Serious eye damage/eye irritation Category 2A > 5 - < 10 % | >= 3 - < 5 |
| monoethanolamine | 141-43-5 205-483-3 01-2119486455-28 | Acute toxicity Category 4; H302 Acute toxicity Category 4; H332 Acute toxicity Category 4; H312 Skin corrosion Sub-category 1B; H314 Chronic aquatic toxicity Category 3; H412 Specific target organ toxicity - single exposure Category 3; H335 Specific target organ toxicity - single exposure Category 3 H335 5 - 100 % | >= 3 - < 5 |
| Amines, C12-14 alkyldimethyl, N-oxides | 308062-28-4 01-2119490061-47 | Acute toxicity Category 4; H302 Skin irritation Category 2; H315 Serious eye damage Category 1; H318 Acute aquatic toxicity Category 1; H400 Chronic aquatic toxicity Category 2; H411 | >= 0.5 - < 1 |

GREASELIFT

M = 1

**Product AT USE DILUTION
Hazardous components**

| Chemical Name | CAS-No. EC-No. REACH No. | Classification REGULATION (EC) No 1272/2008 | Concentration : [%] |
|---|--|--|------------------------|
| Benzyl alcohol | 100-51-6 202-859-9 01-2119492630-38 | Acute toxicity Category 4; H302 Acute toxicity Category 4; H332 Serious eye damage/eye irritation Category 2; H319 | >= 5 - < 10 |
| 2-butoxyethanol | 111-76-2 203-905-0 01-2119475108-36 | Acute toxicity Category 4; H302 Acute toxicity Category 3; H331 Skin irritation Category 2; H315 Eye irritation Category 2; H319 | >= 1 - < 2.5 |
| 9-octadecenoic acid (z)-, compd. with 2- aminoethanol (1:1) | 2272-11-9 218-878-0 01-2119958940-28 | Eye irritation Category 2; H319 | >= 1 - < 2.5 |
| Dodecyldimethylamine oxide | 1643-20-5 216-700-6 01-2120068065-58 | Acute toxicity Category 4; H302 Skin irritation Category 2; H315 Serious eye damage Category 1; H318 Acute aquatic toxicity Category 1; H400 Chronic aquatic toxicity Category 2; H411 | >= 0.1 - < 0.25 |
| Substances with a workplace exposure limit : | | | |
| monoethanolamine | 141-43-5 205-483-3 01-2119486455-28 | Acute toxicity Category 4; H302 Acute toxicity Category 4; H332 Acute toxicity Category 4; H312 Skin corrosion Sub-category 1B; H314 Chronic aquatic toxicity Category 3; H412 Specific target organ toxicity - single exposure Category 3; H335 Specific target organ toxicity - single exposure Category 3 H335 5 - 100 % | >= 0.5 - < 1 |

For the full text of the H-Statements mentioned in this Section, see Section 16.

Section: 4. FIRST AID MEASURES**4.1 Description of first aid measures****Product AS SOLD**

- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.
- In case of skin contact : Wash off immediately with plenty of water for at least 15 minutes. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.
- If swallowed : Rinse mouth with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention immediately.

GREASELIFT

If inhaled : Remove to fresh air. Treat symptomatically. Get medical attention.

Product AT USE DILUTION

In case of eye contact : Rinse with plenty of water.

In case of skin contact : Rinse with plenty of water.

If swallowed : Rinse mouth. Get medical attention if symptoms occur.

If inhaled : Get medical attention if symptoms occur.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

4.3 Indication of immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

Section: 5. FIREFIGHTING MEASURES

Product AS SOLD

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media : None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Not flammable or combustible.

Hazardous combustion products : Depending on combustion properties, decomposition products may include following materials:
Carbon oxides
nitrogen oxides (NOx)
Sulphur oxides
metal oxides

5.3 Advice for firefighters

Special protective equipment for firefighters : Use personal protective equipment.

Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire and/or explosion do not breathe fumes.

Section: 6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Product AS SOLD

GREASELIFT

Advice for non-emergency personnel : Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in sections 7 and 8.

Advice for emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.

Product AT USE DILUTION

Advice for non-emergency personnel : Refer to protective measures listed in sections 7 and 8.

Advice for emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.

6.2 Environmental precautions

Product AS SOLD

Environmental precautions : Do not allow contact with soil, surface or ground water.

Product AT USE DILUTION

Environmental precautions : No special environmental precautions required.

6.3 Methods and materials for containment and cleaning up

Product AS SOLD

Methods for cleaning up : Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

Product AT USE DILUTION

Methods for cleaning up : Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

6.4 Reference to other sections

See Section 1 for emergency contact information.
For personal protection see section 8.
See Section 13 for additional waste treatment information.

Section: 7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Product AS SOLD

Advice on safe handling : Do not ingest. Do not get in eyes, on skin, or on clothing. Use only with adequate ventilation. Wash hands thoroughly after handling. Do not breathe spray, vapour. In case of mechanical malfunction, or if in contact with unknown dilution of product, wear full Personal

GREASELIFT

Protective Equipment (PPE).

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

Product AT USE DILUTION

Advice on safe handling : Wash hands after handling. In case of mechanical malfunction, or if in contact with unknown dilution of product, wear full Personal Protective Equipment (PPE). For personal protection see section 8.

Hygiene measures : Wash hands before breaks and immediately after handling the product.

7.2 Conditions for safe storage, including any incompatibilities

Product AS SOLD

Requirements for storage areas and containers : Keep out of reach of children. Keep container tightly closed. Store in suitable labeled containers.

Storage temperature : 5 °C to 40 °C

Product AT USE DILUTION

Requirements for storage areas and containers : Keep out of reach of children. Keep container tightly closed. Store in suitable labeled containers.

7.3 Specific end uses

Product AS SOLD

Section: 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Product AS SOLD

Occupational Exposure Limits

| Components | CAS-No. | Value type (Form of exposure) | Control parameters | Basis |
|---------------------|----------|---|---------------------------------|------------|
| 2-butoxyethanol | 111-76-2 | TWA | 25 ppm 123 mg/m ³ | UKCOSSTD |
| Further information | Sk | Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. | | |
| | | STEL | 50 ppm 246 mg/m ³ | UKCOSSTD |
| Further information | Sk | Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. | | |
| | | TWA | 20 ppm 98 mg/m ³ | 2000/39/EC |
| Further information | skin | Identifies the possibility of significant uptake through the skin | | |
| | | Indicative | | |
| | | STEL | 50 ppm 246 mg/m ³ | 2000/39/EC |
| Further information | skin | Identifies the possibility of significant uptake through the skin | | |
| | | Indicative | | |
| monoethanolamine | 141-43-5 | TWA | 1 ppm 2.5 mg/m ³ | UKCOSSTD |

GREASELIFT

| | | | | |
|---------------------|------|---|--------------------|------------|
| Further information | Sk | Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. | | |
| | | STEL | 3 ppm 7.6 mg/m3 | UKCOSSTD |
| Further information | Sk | Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. | | |
| | | TWA | 1 ppm 2.5 mg/m3 | 2006/15/EC |
| Further information | | Indicative | | |
| | skin | Identifies the possibility of significant uptake through the skin | | |
| | | STEL | 3 ppm 7.6 mg/m3 | 2006/15/EC |
| Further information | | Indicative | | |
| | skin | Identifies the possibility of significant uptake through the skin | | |

Biological occupational exposure limits

| Substance name | CAS-No. | Control parameters | Sampling time | Basis |
|-----------------|----------|--|---------------|-------------|
| 2-butoxyethanol | 111-76-2 | butoxyacetic acid: 240 Millimoles per mole Creatinine (Urine) | After shift | GB EH40 BAT |

DNEL

| | | |
|--|---|---|
| triethanolamine | : | <p>End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 1 mg/m3</p> <p>End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term local effects Value: 1 mg/m3</p> <p>End Use: Workers Exposure routes: Dermal Potential health effects: Long-term systemic effects Value: 7.5 mg/cm2</p> <p>End Use: Consumers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 1.25 mg/m3</p> <p>End Use: Consumers Exposure routes: Inhalation Potential health effects: Long-term local effects Value: 1.25 mg/m3</p> <p>End Use: Consumers Exposure routes: Dermal Potential health effects: Long-term systemic effects Value: 3.1 mg/cm2</p> <p>End Use: Consumers Exposure routes: Ingestion Potential health effects: Long-term systemic effects Value: 13 ppm</p> |
| Linear(C12-C14)alkanol, ethoxylated, sulfated, sodium salt | : | <p>End Use: Workers Exposure routes: Inhalation</p> |

GREASELIFT

| | |
|--|---|
| | <p>Potential health effects: Long-term systemic effects Value: 175 mg/m³</p> <p>End Use: Workers Exposure routes: Dermal Potential health effects: Long-term systemic effects Value: 2750 mg/m³</p> <p>End Use: Workers Exposure routes: Dermal Potential health effects: Long-term local effects Value: 0.132 mg/m³</p> <p>End Use: Consumers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 52 mg/m³</p> <p>End Use: Consumers Exposure routes: Dermal Potential health effects: Long-term systemic effects Value: 1650 mg/m³</p> <p>End Use: Consumers Exposure routes: Dermal Potential health effects: Long-term local effects Value: 0.079 mg/m³</p> <p>End Use: Consumers Exposure routes: Oral Potential health effects: Long-term systemic effects Value: 15 mg/m³</p> |
|--|---|

PNEC

| | |
|--|---|
| <p>triethanolamine</p> | <p>: Fresh water Value: 0.32 mg/l</p> <p>Marine water Value: 0.032 mg/l</p> <p>Intermittent use/release Value: 5.12 mg/l</p> <p>Fresh water sediment Value: 1.7 mg/kg</p> <p>Marine sediment Value: 1.7 mg/kg</p> <p>Sewage treatment plant Value: 10 mg/l</p> <p>Soil Value: 0.151 mg/kg</p> |
| <p>Linear(C12-C14)alkanol, ethoxylated, sulfated, sodium</p> | <p>: Fresh water</p> |

GREASELIFT

| | |
|------|---|
| salt | Value: 0.24 mg/l Marine water Value: 0.024 mg/l Sewage treatment plant Value: 10000 mg/l Fresh water sediment Value: 0.917 mg/kg Marine sediment Value: 0.092 mg/kg Soil Value: 7.5 mg/kg |
|------|---|

8.2 Exposure controls

Product AS SOLD

Appropriate engineering controls

Engineering measures : Effective exhaust ventilation system. Maintain air concentrations below occupational exposure standards.

Individual protection measures

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

Eye/face protection (EN 166) : Safety goggles
Face-shield

Hand protection (EN 374) : Recommended preventive skin protection
Gloves
Nitrile rubber
butyl-rubber
Breakthrough time: 1 – 4 hours
Minimum thickness for butyl-rubber 0.7 mm for nitrile rubber 0.4 mm or equivalent (please refer to the gloves manufacturer/distributor for advise).
Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Skin and body protection (EN 14605) : Personal protective equipment comprising: suitable protective gloves, safety goggles and protective clothing including appropriate safety shoes

Respiratory protection (EN 143, 14387) : None required if airborne concentrations are maintained below the exposure limit listed in Exposure Limit Information. Use certified respiratory protection equipment meeting EU requirements(89/656/EEC, (EU) 2016/425), or equivalent, when respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods

GREASELIFT

or procedures of work organization.

Product AT USE DILUTION

Appropriate engineering controls

Engineering measures : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Hygiene measures : Wash hands before breaks and immediately after handling the product.

Eye/face protection (EN 166) : No special protective equipment required.

Hand protection (EN 374) : No special protective equipment required.

Skin and body protection (EN 14605) : No special protective equipment required.

Respiratory protection (EN 143, 14387) : None required if airborne concentrations are maintained below the exposure limit listed in Exposure Limit Information. Use certified respiratory protection equipment meeting EU requirements(89/656/EEC, (EU) 2016/425), or equivalent, when respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods or procedures of work organization.

Environmental exposure controls

General advice : Consider the provision of containment around storage vessels.

Section: 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

| | Product AS SOLD | Product AT USE DILUTION |
|---|--|--------------------------------|
| Appearance | : liquid | liquid |
| Colour | : clear, orange | light orange |
| Odour | : slight | slight |
| pH | : 10.5 - 11.5, 100 % | 10.1 - 10.9 |
| Flash point | : 96 °C closed cup, Does not sustain combustion. | |
| Odour Threshold | : Not applicable and/or not determined for the mixture | |
| Melting point/freezing point | : Not applicable and/or not determined for the mixture | |
| Initial boiling point and boiling range | : > 100 °C | |
| Evaporation rate | : Not applicable and/or not determined for the mixture | |
| Flammability (solid, gas) | : Not applicable and/or not determined for the mixture | |
| Upper explosion limit | : Not applicable and/or not determined for the mixture | |
| Lower explosion limit | : Not applicable and/or not determined for the mixture | |
| Vapour pressure | : Not applicable and/or not determined for the mixture | |

GREASELIFT

| | |
|--|--|
| Relative vapour density | : Not applicable and/or not determined for the mixture |
| Relative density | : 1.04 - 1.06 |
| Water solubility | : Not applicable and/or not determined for the mixture |
| Solubility in other solvents | : Not applicable and/or not determined for the mixture |
| Partition coefficient: n-octanol/water | : Not applicable and/or not determined for the mixture |
| Auto-ignition temperature | : Not applicable and/or not determined for the mixture |
| Thermal decomposition | : Not applicable and/or not determined for the mixture |
| Viscosity, kinematic | : Not applicable and/or not determined for the mixture |
| Explosive properties | : Not applicable and/or not determined for the mixture |
| Oxidizing properties | : The substance or mixture is not classified as oxidizing. |

9.2 Other information

Not applicable and/or not determined for the mixture

Section: 10. STABILITY AND REACTIVITY

Product AS SOLD

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

None known.

10.5 Incompatible materials

Acids
Metals

10.6 Hazardous decomposition products

Depending on combustion properties, decomposition products may include following materials:
Carbon oxides
nitrogen oxides (NOx)
Sulphur oxides
metal oxides

Section: 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Product AS SOLD

GREASELIFT

Information on likely routes of exposure : Inhalation, Eye contact, Skin contact

Product

- Acute oral toxicity : Acute toxicity estimate : > 2,000 mg/kg
- Acute inhalation toxicity : 4 h Acute toxicity estimate : 1.96 mg/l
Test atmosphere: dust/mist
- Acute dermal toxicity : Acute toxicity estimate : > 2,000 mg/kg
- Skin corrosion/irritation : There is no data available for this product.
- Serious eye damage/eye irritation : There is no data available for this product.
- Respiratory or skin sensitization : There is no data available for this product.
- Carcinogenicity : There is no data available for this product.
- Reproductive effects : There is no data available for this product.
- Germ cell mutagenicity : There is no data available for this product.
- Teratogenicity : There is no data available for this product.
- STOT - single exposure : The substance or mixture is not classified as specific target organ toxicant, single exposure.
- STOT - repeated exposure : There is no data available for this product.
- Aspiration toxicity : There is no data available for this product.

Components

- Acute oral toxicity : Benzyl alcohol LD50 rat: 1,620 mg/kg
- 2-butoxyethanol LD50 rat: 1,500 mg/kg
- 9-octadecenoic acid (z)-, compd. with 2-aminoethanol (1:1) LD50 rat: > 2,000 mg/kg
- Poly(oxy-1,2-ethanediyl), .alpha.-(phenylmethyl)-.omega.-hydroxy-LD50 rat: > 2,000 mg/kg
- isopropanolamine LD50 rat: > 2,000 mg/kg
- 2-(2-aminoethoxy)ethanol LD50 rat: 3,400 mg/kg
- Benzenesulfonic acid, C10-16-alkyl derivs., potassium salts LD50 rat: 1,249 mg/kg
- Linear(C12-C14)alkanol, ethoxylated, sulfated, sodium salt LD50 rat: 3,350 mg/kg
- monoethanolamine LD50 rat: 1,089 mg/kg
- Amines, C12-14 alkyldimethyl, N-oxides LD50 rat: 1,064 mg/kg

GREASELIFT

Components

Acute inhalation toxicity : isopropanolamine 4 h LC50 rat: > 5.19 mg/l
Test atmosphere: dust/mist

Benzenesulfonic acid, C10-16-alkyl derivs., potassium salts 4 h
LC50 rat: > 1.9 mg/l
Test atmosphere: dust/mist

monoethanolamine 4 h LC50 rat: > 1.6 mg/l
Test atmosphere: dust/mist

Components

Acute dermal toxicity : 9-octadecenoic acid (z)-, compd. with 2-aminoethanol (1:1) LD50
rabbit: > 2,000 mg/kg

Linear(C12-C14)alkanol, ethoxylated, sulfated, sodium salt LD50
rat: 8,000 mg/kg

monoethanolamine LD50 rabbit: 1,025 mg/kg

Potential Health Effects

Product AS SOLD

Eyes : Causes serious eye damage.

Skin : Causes severe skin burns.

Ingestion : Causes digestive tract burns.

Inhalation : Harmful if inhaled. May cause nose, throat, and lung irritation.

Chronic Exposure : Health injuries are not known or expected under normal use.

Product AT USE DILUTION

Eyes : Health injuries are not known or expected under normal use.

Skin : Health injuries are not known or expected under normal use.

Ingestion : Health injuries are not known or expected under normal use.

Inhalation : Health injuries are not known or expected under normal use.

Chronic Exposure : Health injuries are not known or expected under normal use.

Experience with human exposure

Product AS SOLD

Eye contact : Redness, Pain, Corrosion

Skin contact : Redness, Pain, Corrosion

Ingestion : Corrosion, Abdominal pain

Inhalation : Respiratory irritation, Cough

Product AT USE DILUTION

Eye contact : No symptoms known or expected.

GREASELIFT

Skin contact : No symptoms known or expected.
Ingestion : No symptoms known or expected.
Inhalation : No symptoms known or expected.

Section: 12. ECOLOGICAL INFORMATION

12.1 Toxicity

Product AS SOLD

Environmental Effects : This product has no known ecotoxicological effects.

Product AT USE DILUTION

Environmental Effects : This product has no known ecotoxicological effects.

Product AS SOLD

Product

Toxicity to fish : no data available
Toxicity to daphnia and other aquatic invertebrates : no data available
Toxicity to algae : no data available

Components

Toxicity to fish : Benzyl alcohol 96 h LC50 Pimephales promelas (fathead minnow): 460 mg/l
2-butoxyethanol 96 h LC50 Fish: > 100 mg/l
9-octadecenoic acid (z)-, compd. with 2-aminoethanol (1:1) 96 h LC50 Fish: 7.44 mg/l
Poly(oxy-1,2-ethanediyl), .alpha.-(phenylmethyl)-.omega.-hydroxy- 96 h LC50: > 100 mg/l
2-(2-aminoethoxy)ethanol 96 h LC50 Leuciscus idus (Golden orfe): 460 mg/l
Benzenesulfonic acid, C10-16-alkyl derivs., potassium salts 96 h LC50 Fish: 5.07 mg/l
Linear(C12-C14)alkanol, ethoxylated, sulfated, sodium salt 96 h LC50 Danio rerio (zebra fish): 7.1 mg/l
Amines, C12-14 alkyldimethyl, N-oxides 96 h LC50: 2.67 mg/l

Components

Toxicity to daphnia and other aquatic invertebrates : Benzyl alcohol 48 h EC50 Daphnia magna (Water flea): 230 mg/l
2-(2-aminoethoxy)ethanol 48 h EC50 Daphnia magna (Water flea): 189 mg/l
Linear(C12-C14)alkanol, ethoxylated, sulfated, sodium salt 48 h EC50 Daphnia magna (Water flea): 7.4 mg/l

GREASELIFT

monoethanolamine 48 h LC50 Daphnia magna (Water flea): 65 mg/l

Amines, C12-14 alkyldimethyl, N-oxides 48 h EC50 Daphnia magna (Water flea): 3.1 mg/l

Components

Toxicity to algae

: Benzyl alcohol 72 h EC50 Pseudokirchneriella subcapitata (green algae): 770 mg/l

2-butoxyethanol 72 h EC50 Aquatic Plant: 911 mg/l

isopropanolamine 72 h EC50: 32.7 mg/l

2-(2-aminoethoxy)ethanol 72 h EC50 Desmodesmus subspicatus (green algae): 202 mg/l

Linear(C12-C14)alkanol, ethoxylated, sulfated, sodium salt 72 h EC50 Desmodesmus subspicatus (green algae): 27.7 mg/l

Amines, C12-14 alkyldimethyl, N-oxides 72 h LC50: 0.143 mg/l
72 h NOEC: 0.067 mg/l

12.2 Persistence and degradability

Product

Biodegradability

: The surfactants contained in the product are biodegradable according to the requirements of the detergent regulation 648/2004/EC

Components

Biodegradability

: Benzyl alcohol Result: Readily biodegradable.

2-butoxyethanol Result: Readily biodegradable.

9-octadecenoic acid (z)-, compd. with 2-aminoethanol (1:1) Result: Readily biodegradable.

Poly(oxy-1,2-ethanediyl), .alpha.-(phenylmethyl)-.omega.-hydroxy- Result: Readily biodegradable.

isopropanolamine Result: Readily biodegradable.

2-(2-aminoethoxy)ethanol Result: Biodegradable

Benzenesulfonic acid, C10-16-alkyl derivs., potassium salts Result: Readily biodegradable.

Linear(C12-C14)alkanol, ethoxylated, sulfated, sodium salt Result: Readily biodegradable.

monoethanolamine Result: Readily biodegradable.

Amines, C12-14 alkyldimethyl, N-oxides Result: Readily biodegradable.

GREASELIFT

12.3 Bioaccumulative potential

no data available

12.4 Mobility in soil

no data available

12.5 Results of PBT and vPvB assessment

Product

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

no data available

Section: 13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with the European Directives on waste and hazardous waste. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

13.1 Waste treatment methods

Product AS SOLD

Product : Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of contents/container in accordance with local regulations. Dispose of wastes in an approved waste disposal facility.

Contaminated packaging : Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local, state, and federal regulations.

Guidance for Waste Code selection : Organic wastes containing dangerous substances. If this product is used in any further processes, the final user must redefine and assign the most appropriate European Waste Catalogue Code. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable European (EU Directive 2008/98/EC) and local regulations.

Product AT USE DILUTION

Product : Diluted product can be flushed to sanitary sewer if regulations permit.

Contaminated packaging : Dispose of in accordance with local, state, and federal regulations.

Section: 14. TRANSPORT INFORMATION

GREASELIFT

Product AS SOLD

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

Land transport (ADR/ADN/RID)

14.1 UN number : 3267
14.2 UN proper shipping name : CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S.
(2-(2-aminoethoxy)ethanol, isopropanolamine)
14.3 Transport hazard class(es) : 8
14.4 Packing group : III
14.5 Environmental hazards : No
14.6 Special precautions for user : None

Air transport (IATA)

14.1 UN number : 3267
14.2 UN proper shipping name : Corrosive liquid, basic, organic, n.o.s.
(2-(2-aminoethoxy)ethanol, isopropanolamine)
14.3 Transport hazard class(es) : 8
14.4 Packing group : III
14.5 Environmental hazards : No
14.6 Special precautions for user : None

Sea transport (IMDG/IMO)

14.1 UN number : 3267
14.2 UN proper shipping name : CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S.
(2-(2-aminoethoxy)ethanol, isopropanolamine)
14.3 Transport hazard class(es) : 8
14.4 Packing group : III
14.5 Environmental hazards : No
14.6 Special precautions for user : None
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code : Not applicable.

Section: 15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

according to Detergents Regulation EC 648/2004 : 5 % or over but less than 15 %: Anionic surfactants, Soap
less than 5 %: Non-ionic surfactants
Other constituents: Perfumes
Allergens:
Benzyl alcohol

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major- : Not applicable.

GREASELIFT

accident hazards involving dangerous substances.

Candidate List of Substances : Not applicable.
of Very High Concern for Authorisation

National Regulations

Take note of Dir 94/33/EC on the protection of young people at work.

Other regulations : The Chemicals (Hazard Information and Packaging for Supply) Regulations.
The Control of Substances Hazardous to Health Regulations.
Health and Safety at Work Act.

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out on the product.

Section: 16. OTHER INFORMATION

Procedure used to derive the classification according to REGULATION (EC) No 1272/2008

| Classification | Justification |
|----------------------------|-------------------------------------|
| Acute toxicity 4, H332 | Calculation method |
| Skin corrosion 1, H314 | Based on product data or assessment |
| Serious eye damage 1, H318 | Based on product data or assessment |

Full text of H-Statements

H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H331 Toxic if inhaled.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H400 Very toxic to aquatic life.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing

GREASELIFT

Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECl - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Prepared by : Regulatory Affairs

Numbers quoted in the MSDS are given in the format: 1,000,000 = 1 million and 1,000 = 1 thousand. 0.1 = 1 tenth and 0.001 = 1 thousandth

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Annex: Exposure Scenarios

Exposure Scenario: Oven/Grill Cleaner. Manual process

Life Cycle Stage : Widespread use by professional workers
Product category : **PC35** Washing and cleaning products (including solvent based products)

Contributing scenario controlling environmental exposure for:

Environmental release category : **ERC8a** Wide dispersive indoor use of processing aids in open systems
Daily amount per site : 7.5 kg
Type of Sewage Treatment Plant : Municipal sewage treatment plant

Contributing scenario controlling worker exposure for:

GREASELIFT

Process category : **PROC10** Roller application or brushing

Exposure duration : 480 min

Operational conditions and risk management measures : Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Respiratory Protection : see section 8

Skin Protection : see section 8

Exposure Scenario: Oven/Grill Cleaner. Spray and wipe manual process

Life Cycle Stage : Widespread use by professional workers

Product category : **PC35** Washing and cleaning products (including solvent based products)

Contributing scenario controlling environmental exposure for:

Environmental release category : **ERC8a** Wide dispersive indoor use of processing aids in open systems

Daily amount per site : 7.5 kg

Type of Sewage Treatment Plant : Municipal sewage treatment plant

Contributing scenario controlling worker exposure for:

Process category : **PROC10** Roller application or brushing

Exposure duration : 480 min

Operational conditions and risk management measures : Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Respiratory Protection : see section 8

Skin Protection : see section 8

Contributing scenario controlling worker exposure for:

Process category : **PROC11** Non industrial spraying

Exposure duration : 60 min

Operational conditions and risk management measures : Indoor

GREASELIFT

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : see section 8

Respiratory Protection : see section 8

Exposure Scenario: Kitchen cleaner. Manual process

Life Cycle Stage : Widespread use by professional workers

Product category : **PC35** Washing and cleaning products (including solvent based products)

Contributing scenario controlling environmental exposure for:

Environmental release category : **ERC8a** Wide dispersive indoor use of processing aids in open systems

Daily amount per site : 7.5 kg

Type of Sewage Treatment Plant : Municipal sewage treatment plant

Contributing scenario controlling worker exposure for:

Process category : **PROC10** Roller application or brushing

Exposure duration : 480 min

Operational conditions and risk management measures : Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : see section 8

Respiratory Protection : see section 8

Contributing scenario controlling worker exposure for:

Process category : **PROC8a** Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities

Exposure duration : 60 min

Operational conditions and risk management measures : Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : see section 8

GREASELIFT

Respiratory Protection : see section 8

Exposure Scenario: Kitchen cleaner. Manual process

Life Cycle Stage : Widespread use by professional workers

Product category : **PC35** Washing and cleaning products (including solvent based products)

Contributing scenario controlling environmental exposure for:

Environmental release category : **ERC8a** Wide dispersive indoor use of processing aids in open systems

Daily amount per site : 7.5 kg

Type of Sewage Treatment Plant : Municipal sewage treatment plant

Contributing scenario controlling worker exposure for:

Process category : **PROC10** Roller application or brushing

Exposure duration : 480 min

Operational conditions and risk management measures : Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : see section 8

Respiratory Protection : see section 8

Contributing scenario controlling worker exposure for:

Process category : **PROC8a** Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities

Exposure duration : 60 min

Operational conditions and risk management measures : Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : see section 8

Respiratory Protection : see section 8