

Section: 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

	Product name	:	KEYSTONE DEGREASER HD		
	Product code	:	123075E		
	Use of the Substance/Mixture	:	All Purpose Cleaner		
	Substance type:	:	Mixture		
			For professional users only.		
	Product dilution information	•	No dilution information provided.		
1.2	1.2 Relevant identified uses of the substance or mixture and uses advised against				
	Identified uses	:	Kitchen cleaner. Manual process Kitchen cleaner. Spray and wipe manual process		
	Recommended restrictions on use	:	Reserved for industrial and professional use.		
1.3	1.3 Details of the supplier of the safety data sheet				
	-				

Company	: Ecolab Ltd.
	PO Box 11; Winnington Avenue
	Northwich, Cheshire, United Kingdom CW8 4DX
	+ 44 (0)1606 74488
	ccs@ecolab.com

1.4 Emergency telephone number

Emergency telephone number	:	+441618841235 +32-(0)3-575-5555 Trans-European
Poison Information Centre telephone number	:	For medical professionals only: 0344 892 0111

Date of Compilation/Revision : 22.01.2025 Version : 1.0

Section: 2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2	H315
Eye irritation, Category 2	H319

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms		
Signal Word	: Warning	
Hazard Statements	: H315 H319	Causes skin irritation. Causes serious eye irritation.
Precautionary Statements	: Prevention: P280	Wear protective gloves/ eye protection/ face protection.

2.3 Other hazards

None known. Section: 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixtures

Hazardous components

Chamical Nama		Classification	Concentration
Chemical Name	CAS-No. EC-No.	REGULATION (EC) No 1272/2008	Concentration : [%]
	REACH No.		
2-(2-butoxyethoxy)ethanol	112-34-5	Eye irritation Category 2; H319	>= 1 - < 10
	203-961-6		
	01-2119475104-44		
Benzenesulfonic acid, 4-	85536-14-7	Acute toxicity Category 4; H302	>= 2.5 - < 3
C10-13-sec-alkyl derivs	287-494-3	Skin corrosion Category 1C; H314	
	01-2119490234-40	Serious eye damage Category 1; H318	
	0	Chronic aquatic toxicity Category 3; H412	
Sodium silicate	1344-09-8	Corrosive to metals Category 1; H290	>= 1 - < 3
	215-687-4	Skin corrosion Sub-category 1B; H314	_
	01-2119448725-31	Serious eye damage Category 1; H318	
		Specific target organ toxicity - single	
		exposure Category 3; H335	
		Serious eye damage/eye irritation	
		Category 1	
		28 - 100 %	
		Serious eye damage/eye irritation	
		Category 2A	
		24 - < 28 %	
		Skin corrosion/irritation Category 1B	
		39 - 100 %	
		Skin corrosion/irritation Category 2	
		24 - < 39 %	
		Specific target organ toxicity - single	
		exposure Category 3	
		24 - 100 %	
		Corrosive to metals Category 1	
		39 - 100 %	
			1

For the full text of the H-Statements mentioned in this Section, see Section 16. Section: 4. FIRST AID MEASURES

4.1 Description of first aid measures

In case of eye contact	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention.
In case of skin contact	:	Wash off immediately with plenty of water for at least 15 minutes. Use a mild soap if available. Get medical attention if irritation develops and persists.
If swallowed	:	Rinse mouth. Get medical attention if symptoms occur.
If inhaled	:	Get medical attention if symptoms occur.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

4.3 Indication of immediate medical attention and special treatment needed

Treatment	: Treat symptomatically.
-----------	--------------------------

Section: 5. FIREFIGHTING MEASURES

5.1 Extinguishing media

	Suitable extinguishing media	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.				
	Unsuitable extinguishing media	:	None known.				
5.2	5.2 Special hazards arising from the substance or mixture						
	Specific hazards during firefighting	:	Not flammable or combustible.				
	Hazardous combustion products	:	Depending on combustion properties, decomposition products may include following materials: Carbon oxides Sulphur oxides				
5.3	5.3 Advice for firefighters						
	Special protective equipment for firefighters	:	Use personal protective equipment.				

Further information: Fire residues and contaminated fire extinguishing water must be
disposed of in accordance with local regulations. In the event of
fire and/or explosion do not breathe fumes.

Section: 6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel	:	Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in sections 7 and 8.
Advice for emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.

6.2 Environmental precautions

Environmental precautions : Do not allow contact with soil, surface or ground water.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up	:	Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.
-------------------------	---	---

6.4 Reference to other sections

See Section 1 for emergency contact information. For personal protection see section 8. See Section 13 for additional waste treatment information.

Section: 7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Advice on safe handling	Avoid contact with skin and eyes. Use only with adequate ventilation. Wash hands thoroughly after handling. In case of mechanical malfunction, or if in contact with unknown dilution product, wear full Personal Protective Equipment (PPE).	
Hygiene measures	Handle in accordance with good industrial hygiene and safet practice. Remove and wash contaminated clothing before re Wash face, hands and any exposed skin thoroughly after handling.	

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers	:	Protect from frost, heat and sunlight. Store at room temperature in the original container. Keep out of reach of children. Keep container tightly closed. Store in suitable labeled containers.
Storage temperature	:	5 °C to 35 °C

7.3 Specific end uses

Specific use(s)	: Kitchen cleaner. Manual process
	Kitchen cleaner. Spray and wipe manual process

Section: 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
2-(2- butoxyethoxy)ethanol	112-34-5	TWA	10 ppm 67.5 mg/m3	UKCOSSTD
		STEL	15 ppm 101.2 mg/m3	UKCOSSTD

DNEL

DNEL		
2-(2-butoxyethoxy)ethanol		End Use: Workers Exposure routes: Inhalation Potential health effects: Short-term - local Value: 101.2 mg/m3 End Use: Workers Exposure routes: Dermal Potential health effects: Long-term systemic effects Value: 20 mg/kg End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 67.5 mg/m3 End Use: Workers Exposure routes: Inhalation Potential health effects: Short-term - local Value: 67.5 mg/m3
Sodium silicate	:	End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 5.61 mg/m3 End Use: Workers Exposure routes: Dermal Potential health effects: Long-term systemic effects Value: 1.59 mg/cm2 End Use: Consumers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 1.38 mg/m3 End Use: Consumers Exposure routes: Dermal Potential health effects: Long-term systemic effects Value: 0.8 mg/cm2 End Use: Consumers Exposure routes: Ingestion Potential health effects: Long-term systemic effects Value: 0.8 mg/cm2
Linear(C12-C14)alkanol, ethoxylated, sulfated, sodium salt	:	End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects

Value: 175 mg/m3
End Use: Workers Exposure routes: Dermal Potential health effects: Long-term systemic effects Value: 2750 mg/m3
End Use: Workers Exposure routes: Dermal Potential health effects: Long-term local effects Value: 0.132 mg/m3
End Use: Consumers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 52 mg/m3
End Use: Consumers Exposure routes: Dermal Potential health effects: Long-term systemic effects Value: 1650 mg/m3
End Use: Consumers Exposure routes: Dermal Potential health effects: Long-term local effects Value: 0.079 mg/m3
End Use: Consumers Exposure routes: Oral Potential health effects: Long-term systemic effects Value: 15 mg/m3

PNEC

PNEC		
2-(2-butoxyethoxy)ethanol		Fresh water
		Value: 1 mg/l
		Marine water
		Value: 0.1 mg/l
		Intermittent use/release
		Value: 3.9 mg/l
		Sewage treatment plant
		Value: 200 mg/l
		Sediment
		Value: 4 mg/kg
		Soil
		Value: 0.4 mg/kg
		Oral Value: 56 mg/kg
		value. So myrky
Sodium silicate	:	Fresh water
		Value: 7.5 mg/l

		Marine water Value: 1 mg/l Intermittent use/release Value: 7.5 mg/l Sewage treatment plant Value: 348 mg/l
Linear(C12-C14)alkanol, ethoxylated, sulfated, sodium salt	:	Fresh water Value: 0.24 mg/l Marine water Value: 0.024 mg/l Sewage treatment plant Value: 10000 mg/l Fresh water sediment Value: 0.917 mg/kg Marine sediment Value: 0.092 mg/kg Soil Value: 7.5 mg/kg

8.2 Exposure controls

Appropriate engineering contr	ols
Engineering measures	Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
Individual protection measures	3
Hygiene measures :	Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling.
Eye/face protection (EN 166)	Safety glasses with side-shields
Hand protection (EN 374) :	Recommended preventive skin protection Gloves Nitrile rubber butyl-rubber Breakthrough time: 1 – 4 hours Minimum thickness for butyl-rubber 0.3 mm for nitrile rubber 0.2 mm or equivalent (please refer to the gloves manufacturer/distributor for advise). Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
Skin and body protection :	No special protective equipment required.

Respiratory protection (EN 143, 14387)	: None required if airborne concentrations are maintained below the exposure limit listed in Exposure Limit Information. Use certified respiratory protection equipment meeting EU requirements(89/656/EEC, (EU) 2016/425), or equivalent, when respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods or procedures of work organization.
Environmental exposure co	ntrols

General advice : Consider the provision of containment around storage vessels.

Section: 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance	:	liquid
Colour	:	clear, light yellow
Odour	:	not significant
рН	:	10.2 - 11.4, 100 %
Flash point	:	Not applicable.
Odour Threshold	:	Not applicable and/or not determined for the mixture
Melting point/freezing point	:	Not applicable and/or not determined for the mixture
Initial boiling point and boiling range	:	Not applicable and/or not determined for the mixture
Evaporation rate	:	Not applicable and/or not determined for the mixture
Flammability (solid, gas)	:	Not applicable and/or not determined for the mixture
Upper explosion limit	:	Not applicable and/or not determined for the mixture
Lower explosion limit	:	Not applicable and/or not determined for the mixture
Vapour pressure	:	Not applicable and/or not determined for the mixture
Relative vapour density	:	Not applicable and/or not determined for the mixture
Relative density	:	1.015 - 1.055
Water solubility	:	soluble
Solubility in other solvents	:	Not applicable and/or not determined for the mixture
Partition coefficient: n- octanol/water	:	Not applicable and/or not determined for the mixture
Auto-ignition temperature	:	Not applicable and/or not determined for the mixture
Thermal decomposition	:	Not applicable and/or not determined for the mixture
Viscosity, kinematic	:	Not applicable and/or not determined for the mixture
Explosive properties	:	Not applicable and/or not determined for the mixture
Oxidizing properties		The substance or mixture is not classified as oxidizing.

9.2 Other information

Not applicable and/or not determined for the mixture

Section: 10. STABILITY AND REACTIVITY

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

None known.

10.5 Incompatible materials

Acids

10.6 Hazardous decomposition products

In the event of fire, see Section 5

Section: 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Information on likely routes of	:	Inhalation, Eye contact, Skin contact
exposure		

Product

Acute oral toxicity	: Acute toxicity estimate : > 2,000 mg/kg
Acute inhalation toxicity	: There is no data available for this product.
Acute dermal toxicity	: There is no data available for this product.
Skin corrosion/irritation	: There is no data available for this product.
Serious eye damage/eye irritation	: There is no data available for this product.
Respiratory or skin sensitization	: There is no data available for this product.
Carcinogenicity	: There is no data available for this product.
Reproductive effects	: There is no data available for this product.
Germ cell mutagenicity	: There is no data available for this product.
Teratogenicity	: There is no data available for this product.

STOT - single exposure	: There is no data available for this product.	
STOT - repeated exposure	: There is no data available for this product.	
Aspiration toxicity	: There is no data available for this product.	
Components		
Acute oral toxicity	: 2-(2-butoxyethoxy)ethanol LD50 rat: 3,306 mg/kg	
	Benzenesulfonic acid, 4-C10-13-sec-alkyl derivs LD50 rat: 1,470 mg/kg	
	Sodium silicate LD50 rat: 3,400 mg/kg	
Components		
Acute dermal toxicity	: 2-(2-butoxyethoxy)ethanol LD50 rabbit: 2,764 mg/kg	
	Sodium silicate LD50 rat: > 5,000 mg/kg Test substance: Information given is based on data obtained from similar substances.	
Potential Health Effects		
Eyes	: Causes serious eye irritation.	
Skin	: Causes skin irritation.	
Ingestion	: Health injuries are not known or expected under normal use.	
Inhalation	: Health injuries are not known or expected under normal use.	
Chronic Exposure	: Health injuries are not known or expected under normal use.	
Experience with human exposure		
Eye contact	: Redness, Pain, Irritation	
Skin contact	: Redness, Irritation	
Ingestion	: No symptoms known or expected.	
Inhalation	: No symptoms known or expected.	

Section: 12. ECOLOGICAL INFORMATION

12.1 Toxicity

Environmental Effects	: This product has no known ecotoxicological effects.
Product	
Toxicity to fish	: no data available
Toxicity to daphnia and other aquatic invertebrates	: no data available
Toxicity to algae	: no data available

Components		
Toxicity to fish	:	2-(2-butoxyethoxy)ethanol96 h LC50 Fish: 1,300 mg/l
		Benzenesulfonic acid, 4-C10-13-sec-alkyl derivs96 h LC50 Fish: 1.67 mg/l
		Sodium silicate96 h LC50 Oncorhynchus mykiss (rainbow trout): 260 mg/l
Components		
Toxicity to daphnia and other aquatic invertebrates	:	Sodium silicate48 h EC50 Daphnia magna (Water flea): 1,700 mg/l
Components		
Toxicity to algae	:	Sodium silicate72 h EC50 Desmodesmus subspicatus (green algae): 207 mg/l
12.2 Persistence and degradabi	lity	
Product		
Biodegradability	:	The surfactants contained in the product are biodegradable according to the requirements of the detergent regulation 648/2004/EC
Components		
Biodegradability	:	2-(2-butoxyethoxy)ethanolResult: Readily biodegradable.
		Benzenesulfonic acid, 4-C10-13-sec-alkyl derivsResult: Readily biodegradable.
		Sodium silicateResult: Not applicable - inorganic
12.3 Bioaccumulative potential		
no data available		
12.4 Mobility in soil		
no data available		
12.5 Results of PBT and vPvB a	sse	essment
Product		
Assessment	:	This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.
12.6 Other adverse effects		

12.6 Other adverse effects

no data available

Section: 13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with the European Directives on waste and hazardous waste.Waste

codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

13.1 Waste treatment methods

Product	re ad	Vhere possible recycling is preferred to disposal or incineration. If ecycling is not practicable, dispose of contents/container in ccordance with local regulations. Dispose of wastes in an pproved waste disposal facility.
Contaminated packaging	to ne	Dispose of as unused product. Empty containers should be taken o an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local, tate, and federal regulations.
Guidance for Waste Code selection	is is to de	Organic wastes containing dangerous substances. If this product is used in any further processes, the final user must redefine and assign the most appropriate European Waste Catalogue Code. It is the responsibility of the waste generator to determine the oxicity and physical properties of the material generated to letermine the proper waste identification and disposal methods in ompliance with applicable European (EU Directive 2008/98/EC) and local regulations.

Section: 14. TRANSPORT INFORMATION

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

Land transport (ADR/ADN/RID)

14.1 UN number	: Not dangerous goods
14.2 UN proper shipping	: Not dangerous goods
name	
14.3 Transport hazard	: Not dangerous goods
class(es)	
14.4 Packing group	: Not dangerous goods
14.5 Environmental hazards	: Not dangerous goods
14.6 Special precautions for	: Not dangerous goods
user	

Air transport (IATA)

14.1 UN number	: Not dangerous goods
14.2 UN proper shipping	: Not dangerous goods
name	
14.3 Transport hazard	: Not dangerous goods
class(es)	
14.4 Packing group	: Not dangerous goods
14.5 Environmental hazards	: Not dangerous goods
14.6 Special precautions for	: Not dangerous goods
user	

Sea transport (IMDG/IMO)

14.1 UN number	: Not dangerous goods
14.2 UN proper shipping	: Not dangerous goods
name	

14.3 Transport hazard class(es)	: Not dangerous goods
14.4 Packing group	: Not dangerous goods
14.5 Environmental hazards	: Not dangerous goods
14.6 Special precautions for	: Not dangerous goods
user	
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	: Not dangerous goods

Section: 15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

according to Detergents	:	less than 5 %: Anionic surfactants
Regulation EC 648/2004		

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major- accident hazards involving dangerous substances.	:		Not applicable.
Candidate List of Substances of Very High Concern for Authorisation	:		Not applicable.
National Regulations			
Take note of Dir 94/33/EC or	า th	ıe	e protection of young people at work.

Other regulations: The Chemicals (Hazard Information and Packaging for Supply)
Regulations.
The Control of Substances Hazardous to Health Regulations.
Health and Safety at Work Act.

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out on the product. Section: 16. OTHER INFORMATION

Procedure used to derive the classification according to REGULATION (EC) No 1272/2008

Classification	Justification
Skin irritation 2, H315	Calculation method
Eye irritation 2, H319	Calculation method

Full text of H-Statements

H290	May be corrosive to metals.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H412	Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 -Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIOC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN -United Nations; vPvB - Very Persistent and Very Bioaccumulative

Prepared by

: Regulatory Affairs

Numbers quoted in the MSDS are given in the format: 1,000,000 = 1 million and 1,000 = 1 thousand. 0.1 = 1 tenth and 0.001 = 1 thousandth

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Annex: Exposure Scenarios

Exposure Scenario: Kitchen cleaner. Manual process

Life Cycle Stage

: Widespread use by professional workers

Product category	:	PC35	Washing and cleaning products (including solvent based products)			
Contributing scenario contro	Contributing scenario controlling environmental exposure for:					
Environmental release category	:	ERC8a	Wide dispersive indoor use of processing aids in open systems			
Daily amount per site	:	7.5 kg				
Type of Sewage Treatment Plant	:	Municipal s	ewage treatment plant			
Contributing scenario controlling worker exposure for:						
Process category	:	PROC10	Roller application or brushing			
Exposure duration	:	480 min				
Operational conditions and risk management measures	:	Indoor				
		Local Exha	ust Ventilation is not required			
General ventilation		Ventilation	rate per hour 1			
Skin Protection	:	see section	8			
Respiratory Protection	:	see section	8			
Contributing scenario controlling worker exposure for:						
Process category	:	PROC8a	Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non- dedicated facilities			
Exposure duration	:	60 min				
Operational conditions and risk management measures	:	Indoor				
		Local Exhaust Ventilation is not required				
General ventilation		Ventilation	rate per hour 1			
Skin Protection	:	see section 8				
Respiratory Protection	:	see section	8			
Exposure Scenario: Kitchen	cle	aner. Spray	and wipe manual process			
Life Cycle Stage	:	Widespread	d use by professional workers			
Product category	:	PC35	Washing and cleaning products (including solvent based products)			

Contributing scenario controlling environmental exposure for:

Environmental release category	:	ERC8a	Wide dispersive indoor use of processing aids systems	s in open
Daily amount per site	:	7.5 kg		
Type of Sewage Treatment Plant	:	Municipal sewage treatment plant		
Contributing scenario controlling worker exposure for:				
Process category	:	PROC10	Roller application or brushing	
Exposure duration	:	480 min		
Operational conditions and risk management measures	:	Indoor		
		Local Exhaust Ventilation is not required		
General ventilation		Ventilation rate per hour 1		1
Skin Protection	:	see section	8	
Respiratory Protection	:	see section	8	

Contributing scenario controlling worker exposure for:

Process category	:	PROC8a	Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non- dedicated facilities	
Exposure duration	:	60 min		
Operational conditions and risk management measures	:	Indoor		
		Local Exha	ust Ventilation is not required	
General ventilation		Ventilation	rate per hour 1	
Skin Protection	:	see section	8	
Respiratory Protection	:	see section	8	
Contributing scenario controlling worker exposure for:				
Process category	:	PROC11	Non industrial spraying	
Exposure duration	:	60 min		
Operational conditions and risk management measures	:	Indoor		

hok management medoareo				
		Local Exhaust Ventilation is not required		
General ventilation		Ventilation rate per hour	1	
Skin Protection	:	see section 8		

Respiratory Protection : see section 8