Section: 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product name : Pep Active

Product code : 109774E

Use of the : Surface cleaner

Substance/Mixture

Substance type: : Mixture

For professional users only.

Product dilution information : No dilution information provided.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : General purpose cleaner. Spray and wipe manual process

Floor cleaner. Spray and wipe manual process

Recommended restrictions

on use

: Reserved for industrial and professional use.

1.3 Details of the supplier of the safety data sheet

Company : Ecolab Ltd.

PO Box 11; Winnington Avenue

Northwich, Cheshire, United Kingdom CW8 4DX

+ 44 (0)1606 74488 ccs@ecolab.com

1.4 Emergency telephone number

Emergency telephone : +441618841235

number +32-(0)3-575-5555 Trans-European

Poison Information Centre

telephone number

: For medical professionals only: 0344 892 0111

Date of Compilation/Revision : 17.02.2023 Version : 3.0

Section: 2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin corrosion, Category 1 H314 Serious eye damage, Category 1 H318

The classification of this product is based only on its extreme pH value (in accordance with current

109774E 1 / 16

European legislation).

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms

Signal Word : Danger

Hazard Statements : H314 Causes severe skin burns and eye damage.

Supplemental Hazard : EUH071 Corrosive to the respiratory tract.

Statements

Precautionary Statements : Prevention:

P260 Do not breathe vapours.

P280 Wear protective gloves/ eye protection/ face

protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately

all contaminated clothing. Rinse skin with water

or shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water

for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

Hazardous components which must be listed on the label: Alcoholsulphates

2.3 Other hazards

None known.

Section: 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixtures

Hazardous components

Chemical Name	CAS-No.	Classification	Concentration
	EC-No. REACH No.	REGULATION (EC) No 1272/2008	: [%]
Isopropyl Alcohol	67-63-0 200-661-7 01-2119457558-25	Flammable liquids Category 2; H225 Eye irritation Category 2; H319 Specific target organ toxicity - single exposure Category 3; H336	>= 10 - < 20
2-butoxyethanol	111-76-2 203-905-0 01-2119475108-36	Acute toxicity Category 4; H302 Acute toxicity Category 3; H331 Skin irritation Category 2; H315 Eye irritation Category 2; H319	>= 5 - < 10
Alcoholsulphates	90583-19-0 292-217-4	Skin irritation Category 2; H315 Serious eye damage Category 1; H318	>= 3 - < 5

109774E 2 / 16

Benzyl alcohol	100-51-6 202-859-9 01-2119492630-38	Acute toxicity Category 4; H302 Acute toxicity Category 4; H332 Serious eye damage/eye irritation Category 2; H319	>= 2.5 - < 5

For the full text of the H-Statements mentioned in this Section, see Section 16.

Section: 4. FIRST AID MEASURES

4.1 Description of first aid measures

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for

at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.

In case of skin contact : Wash off immediately with plenty of water for at least 15 minutes.

Wash clothing before reuse. Thoroughly clean shoes before

reuse. Get medical attention immediately.

If swallowed : Rinse mouth with water. Do NOT induce vomiting. Never give

anything by mouth to an unconscious person. Get medical

attention immediately.

If inhaled : Remove to fresh air. Treat symptomatically. Get medical attention

if symptoms occur.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

4.3 Indication of immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

Section: 5. FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Unsuitable extinguishing

media

: None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

: Fire Hazard

Keep away from heat and sources of ignition. Flash back possible over considerable distance.

Beware of vapours accumulating to form explosive concentrations.

Vapours can accumulate in low areas.

Hazardous combustion

products

: Depending on combustion properties, decomposition products

may include following materials:

Carbon oxides

nitrogen oxides (NOx)

Sulphur oxides

109774E 3 / 16

Oxides of phosphorus

5.3 Advice for firefighters

for firefighters

Special protective equipment : Use personal protective equipment.

Further information : Fire residues and contaminated fire extinguishing water must be

disposed of in accordance with local regulations. In the event of

fire and/or explosion do not breathe fumes.

Section: 6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency

personnel

: Ensure adequate ventilation. Remove all sources of ignition. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in

sections 7 and 8.

Advice for emergency

responders

: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable

materials.

6.2 Environmental precautions

Environmental precautions : Do not allow contact with soil, surface or ground water.

6.3 Methods and materials for containment and cleaning up

Eliminate all ignition sources if safe to do so. Stop leak if safe to Methods for cleaning up

do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain

material to ensure runoff does not reach a waterway.

6.4 Reference to other sections

See Section 1 for emergency contact information.

For personal protection see section 8.

See Section 13 for additional waste treatment information.

Section: 7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Advice on safe handling : Do not ingest. Do not get in eyes, on skin, or on clothing. Use only

> with adequate ventilation. Keep away from fire, sparks and heated surfaces. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Wash hands thoroughly after handling. Do not breathe spray, vapour. In

> case of mechanical malfunction, or if in contact with unknown dilution of product, wear full Personal Protective Equipment (PPE).

109774E 4/16

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. Remove and wash contaminated clothing before re-use.

Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing

of the eyes and body in case of contact or splash hazard.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Keep away from heat and sources of ignition. Keep away from oxidizing agents. Keep out of reach of children. Keep container

tightly closed. Store in suitable labeled containers.

Storage temperature : -5 °C to 40 °C

7.3 Specific end uses

Specific use(s) : General purpose cleaner. Spray and wipe manual process

Floor cleaner. Spray and wipe manual process

Section: 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.		Value type (Form of exposure)	Control parameters	Basis
Isopropyl Alcohol	67-63-0		TWA	400 ppm 999 mg/m3	UKCOSSTD
			STEL	500 ppm 1,250 mg/m3	UKCOSSTD
2-butoxyethanol	111-76-2		TWA	25 ppm 123 mg/m3	UKCOSSTD
Further information				e skin. The assigned substances at dermal absorption will lead to	
			STEL	50 ppm 246 mg/m3	UKCOSSTD
Further information				e skin. The assigned substances at dermal absorption will lead to	
			TWA	20 ppm 98 mg/m3	2000/39/EC
Further information	skin	Identifies the possibility of significant uptake through the skin Indicative			
		1	STEL	50 ppm 246 mg/m3	2000/39/EC
Further information	skin			gnificant uptake through the skin	
		Indicative			

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
2-butoxyethanol	111-76-2	butoxyacetic acid: 240 Millimoles per mole Creatinine (Urine)	After shift	GB EH40 BAT

DNEL

DINEL		
Isopropyl Alcohol	: End Use: Workers	
	Exposure routes: Dermal	
	Potential health effects: Long-term systemic effects	
	888 mg/kg	

109774E 5 / 16

		End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 500 mg/m3 End Use: Consumers Exposure routes: Dermal Potential health effects: Long-term systemic effects 319 mg/kg End Use: Consumers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 89 mg/m3 End Use: Consumers Exposure routes: Ingestion
		Exposure routes: Ingestion Potential health effects: Long-term systemic effects 26 mg/kg
2-butoxyethanol	:	

PNEC

Isopropyl Alcohol	:	Fresh water Value: 140.9 mg/l
		Marine water Value: 140.9 mg/l
		Intermittent use/release Value: 140.9 mg/l
		Fresh water Value: 552 mg/kg
		Marine sediment Value: 552 mg/kg
		Soil Value: 28 mg/kg
		Sewage treatment plant Value: 2251 mg/l
		Oral Value: 160 mg/kg
2-butoxyethanol		
Z-Duloxyelilarioi		

8.2 Exposure controls

Appropriate engineering controls

Engineering measures : Effective exhaust ventilation system. Maintain air concentrations

below occupational exposure standards.

Individual protection measures

109774E 6 / 16

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. Remove and wash contaminated clothing before re-use.

Wash face, hands and any exposed skin thoroughly after

handling. Provide suitable facilities for quick drenching or flushing

of the eyes and body in case of contact or splash hazard.

Eye/face protection (EN 166) : Safety goggles

Face-shield

Hand protection (EN 374) : Recommended preventive skin protection

> Gloves Nitrile rubber butyl-rubber

Breakthrough time: 1 – 4 hours

Minimum thickness for butyl-rubber 0.7 mm for nitrile rubber 0.4

mm or equivalent (please refer to the gloves

manufacturer/distributor for advise).

Gloves should be discarded and replaced if there is any indication

of degradation or chemical breakthrough.

Skin and body protection

(EN 14605)

: Personal protective equipment comprising: suitable protective

gloves, safety goggles and protective clothing including

appropriate safety shoes

Respiratory protection (EN

143, 14387)

: When respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods or procedures of work organization, consider the use of certified respiratory protection equipment meeting EU requirements (89/656/EEC, (EU) 2016/425), or equivalent, with filter type:A-P

Environmental exposure controls

General advice : Consider the provision of containment around storage vessels.

Section: 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : light yellow Odour : alcohol-like

Hq : 11.5 - 12.5, 100 %

Flash point : 40 °C closed cup, Does not sustain combustion.

Odour Threshold : Not applicable and/or not determined for the mixture Melting point/freezing point : Not applicable and/or not determined for the mixture Initial boiling point and

boiling range

: Not applicable and/or not determined for the mixture

Evaporation rate : Not applicable and/or not determined for the mixture Flammability (solid, gas) : Not applicable and/or not determined for the mixture Upper explosion limit : Not applicable and/or not determined for the mixture Lower explosion limit : Not applicable and/or not determined for the mixture

Vapour pressure : Not applicable and/or not determined for the mixture

109774E 7/16

Relative vapour density : Not applicable and/or not determined for the mixture

Relative density : 0.97 - 0.98
Water solubility : soluble

Solubility in other solvents : Not applicable and/or not determined for the mixture Partition coefficient: n- : Not applicable and/or not determined for the mixture

octanol/water

Auto-ignition temperature : Not applicable and/or not determined for the mixture

Thermal decomposition : Not applicable and/or not determined for the mixture

Viscosity, kinematic : Not applicable and/or not determined for the mixture

Explosive properties : Not applicable and/or not determined for the mixture

Oxidizing properties : The substance or mixture is not classified as oxidizing.

9.2 Other information

Not applicable and/or not determined for the mixture

Section: 10. STABILITY AND REACTIVITY

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Heat, flames and sparks.

10.5 Incompatible materials

None known.

10.6 Hazardous decomposition products

Depending on combustion properties, decomposition products may include following materials: Carbon oxides nitrogen oxides (NOx) Sulphur oxides Oxides of phosphorus

Section: 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Information on likely routes of : Inhalation, Eye contact, Skin contact

exposure

109774E 8 / 16

Product

Acute oral toxicity : Acute toxicity estimate : > 2,000 mg/kg

Acute inhalation toxicity : 4 h Acute toxicity estimate : > 5 mg/l

Test atmosphere: dust/mist

Acute dermal toxicity : Acute toxicity estimate : > 2,000 mg/kg

Skin corrosion/irritation : There is no data available for this product.

Serious eye damage/eye

irritation

: There is no data available for this product.

Respiratory or skin

sensitization

: There is no data available for this product.

Carcinogenicity : There is no data available for this product.

Reproductive effects : There is no data available for this product.

Germ cell mutagenicity : There is no data available for this product.

Teratogenicity : There is no data available for this product.

STOT - single exposure : There is no data available for this product.

STOT - repeated exposure : There is no data available for this product.

Aspiration toxicity : There is no data available for this product.

Components

Acute oral toxicity : Isopropyl Alcohol LD50 rat: 5,840 mg/kg

2-butoxyethanol LD50 rat: 1,500 mg/kg

Alcoholsulphates LD50 rat: 2,175 mg/kg

Benzyl alcohol LD50 rat: 1,620 mg/kg

Components

Acute inhalation toxicity : Isopropyl Alcohol 4 h LC50 rat: > 30 mg/l

Test atmosphere: vapour

Components

Acute dermal toxicity : Isopropyl Alcohol LD50 rabbit: 12,870 mg/kg

Potential Health Effects

Eyes : Causes serious eye damage.

Skin : Causes severe skin burns.

Ingestion : Causes digestive tract burns.

Inhalation : May cause nose, throat, and lung irritation.

109774E 9 / 16

Chronic Exposure : Health injuries are not known or expected under normal use.

Experience with human exposure

Eye contact : Redness, Pain, Corrosion

Skin contact : Redness, Pain, Corrosion

Ingestion : Corrosion, Abdominal pain

Inhalation : Respiratory irritation, Cough

Section: 12. ECOLOGICAL INFORMATION

12.1 Toxicity

Environmental Effects : This product has no known ecotoxicological effects.

Product

Toxicity to fish : no data available

Toxicity to daphnia and other : no data available

aquatic invertebrates

. no data avallable

Toxicity to algae : no data available

Components

Toxicity to fish : Isopropyl Alcohol96 h LC50 Pimephales promelas (fathead

minnow): 9,640 mg/l

2-butoxyethanol96 h LC50 Fish: > 100 mg/l

Benzyl alcohol96 h LC50 Pimephales promelas (fathead minnow):

460 mg/l

Components

Toxicity to daphnia and other

aquatic invertebrates

: Isopropyl Alcohol LC50 Daphnia magna (Water flea): > 10,000

mg/l

Alcoholsulphates48 h EC50: 31 mg/l

Benzyl alcohol48 h EC50 Daphnia magna (Water flea): 230 mg/l

Components

Toxicity to algae : 2-butoxyethanol72 h EC50 Aquatic Plant: 911 mg/l

Benzyl alcohol72 h EC50 Pseudokirchneriella subcapitata (green

algae): 770 mg/l

12.2 Persistence and degradability

Product

Biodegradability : The surfactants contained in the product are biodegradable

according to the requirements of the detergent regulation

648/2004/EC

Components

109774E 10 / 16

Biodegradability : Isopropyl AlcoholResult: Readily biodegradable.

2-butoxyethanolResult: Readily biodegradable.

AlcoholsulphatesResult: Readily biodegradable.

Benzyl alcoholResult: Readily biodegradable.

12.3 Bioaccumulative potential

no data available

12.4 Mobility in soil

no data available

12.5 Results of PBT and vPvB assessment

Product

Assessment : This substance/mixture contains no components considered to be

either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or

higher.

12.6 Other adverse effects

no data available

Section: 13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with the European Directives on waste and hazardous waste. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

13.1 Waste treatment methods

Product : Where possible recycling is preferred to disposal or incineration. If

recycling is not practicable, dispose of contents/container in accordance with local regulations Dispose of wastes in an

approved waste disposal facility.

Contaminated packaging : Dispose of as unused product. Empty containers should be taken

to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local,

state, and federal regulations.

Guidance for Waste Code

selection

: Organic wastes containing dangerous substances. If this product is used in any further processes, the final user must redefine and

assign the most appropriate European Waste Catalogue Code. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable European (EU Directive 2008/98/EC)

and local regulations.

Section: 14. TRANSPORT INFORMATION

109774E 11 / 16

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

Land transport (ADR/ADN/RID)

14.1 UN number : Not dangerous goods 14.2 UN proper shipping : Not dangerous goods

name

14.3 Transport hazard : Not dangerous goods

class(es)

14.4 Packing group : Not dangerous goods 14.5 Environmental hazards : Not dangerous goods 14.6 Special precautions for : Not dangerous goods

user

Air transport (IATA)

14.1 UN number : Not dangerous goods 14.2 UN proper shipping : Not dangerous goods

name

14.3 Transport hazard : Not dangerous goods

class(es)

: Not dangerous goods 14.4 Packing group 14.5 Environmental hazards : Not dangerous goods 14.6 Special precautions for : Not dangerous goods

user

Sea transport (IMDG/IMO)

14.1 UN number : Not dangerous goods 14.2 UN proper shipping : Not dangerous goods

name

14.3 Transport hazard : Not dangerous goods

class(es)

: Not dangerous goods 14.4 Packing group 14.5 Environmental hazards : Not dangerous goods 14.6 Special precautions for : Not dangerous goods

user

14.7 Transport in bulk according to Annex II of

MARPOL 73/78 and the IBC

Code

Section: 15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

: Not dangerous goods

less than 5 %: Anionic surfactants according to Detergents Regulation EC 648/2004 Other constituents: Perfumes

> Allergens: Benzyl alcohol

Seveso III: Directive FLAMMABLE LIQUIDS P5c 2012/18/EU of the European Parliament and of the Council

on the control of majoraccident hazards involving dangerous substances.

Lower tier: 5,000 t Upper tier: 50,000 t

109774E 12/16

National Regulations

Take note of Dir 94/33/EC on the protection of young people at work.

Other regulations : The Chemicals (Hazard Information and Packaging for Supply)

Regulations.

The Control of Substances Hazardous to Health Regulations.

Health and Safety at Work Act.

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out on the product.

Section: 16. OTHER INFORMATION

Procedure used to derive the classification according to REGULATION (EC) No 1272/2008

Classification	Justification
Skin corrosion 1, H314	Based on product data or assessment
Serious eye damage 1, H318	Based on product data or assessment

Full text of H-Statements

H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.

Full text of other abbreviations

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 -Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical

109774E 13 / 16

Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN -United Nations; vPvB - Very Persistent and Very Bioaccumulative

Prepared by : Regulatory Affairs

Numbers quoted in the MSDS are given in the format: 1,000,000 = 1 million and 1,000 = 1 thousand, 0.1 = 1 tenth and 0.001 = 1 thousandth

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Annex: Exposure Scenarios

Exposure Scenario: General purpose cleaner. Spray and wipe manual process

Life Cycle Stage : Widespread use by professional workers

Product category PC35 Washing and cleaning products (including solvent based

products)

Contributing scenario controlling environmental exposure for:

: ERC8a Wide dispersive indoor use of processing aids in open Environmental release

category systems

Daily amount per site : 7.5 kg

Type of Sewage Treatment : Municipal sewage treatment plant

Plant

Contributing scenario controlling worker exposure for:

Process category : PROC10 Roller application or brushing

Exposure duration : 480 min

Operational conditions and risk management measures

: Indoor

Local Exhaust Ventilation is not required

General ventilation 1 Ventilation rate per hour

109774E 14 / 16

Skin Protection : see section 8

Respiratory Protection : see section 8

Contributing scenario controlling worker exposure for:

Process category : **PROC8a** Transfer of substance or preparation (charging/

discharging) from/ to vessels/ large containers at non-

dedicated facilities

Local Exhaust Ventilation is not required

Exposure duration : 60 min

Operational conditions and risk management measures

Indoor

General ventilation Ventilation rate per hour 1

Skin Protection : see section 8

Respiratory Protection : see section 8

Contributing scenario controlling worker exposure for:

Process category : PROC11 Non industrial spraying

Exposure duration : 60 min

Operational conditions and

risk management measures

Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : see section 8

Respiratory Protection : see section 8

Exposure Scenario: Floor cleaner. Spray and wipe manual process

Life Cycle Stage : Widespread use by professional workers

Product category : PC35 Washing and cleaning products (including solvent based

products)

Contributing scenario controlling environmental exposure for:

Environmental release

ERC8a

Wide dispersive indoor use of processing aids in open

systems

Daily amount per site : 7.5 kg

Type of Sewage Treatment

Plant

category

: Municipal sewage treatment plant

109774E 15 / 16

Contributing scenario controlling worker exposure for:

Process category : **PROC10** Roller application or brushing

Indoor

Exposure duration : 480 min

Operational conditions and

risk management measures

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : see section 8

Respiratory Protection : see section 8

Contributing scenario controlling worker exposure for:

Process category : PROC8a Transfer of substance or preparation (charging/

discharging) from/ to vessels/ large containers at non-

dedicated facilities

Exposure duration : 60 min

Operational conditions and

risk management measures

Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : see section 8

Respiratory Protection : see section 8

Contributing scenario controlling worker exposure for:

Process category : PROC11 Non industrial spraying

Exposure duration : 60 min

Operational conditions and risk management measures

Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : see section 8

Respiratory Protection : see section 8

109774E 16 / 16